

型号P/N	L(uH)	DCR(Ω)		I _{rms} (A)	I _{sat} (A)
		Typ	Max		
ASCD0503-3R3M	3.3	0.033	0.10	5.00	5.90
ASCD0503-3R9M	3.9	0.035	0.12	4.10	4.60
ASCD0503-4R7M	4.7	0.050	0.15	4.00	4.70
ASCD0503-5R6M	5.6	0.060	0.20	3.95	4.40
ASCD0503-6R8M	6.8	0.070	0.25	3.82	4.20
ASCD0503-8R2K	8.2	0.080	0.30	3.10	4.00
ASCD0503-100K	10	0.095	0.31	2.65	3.10
ASCD0503-120K	12	0.10	0.35	2.00	3.75
ASCD0503-150K	15	0.12	0.36	2.00	3.70
ASCD0503-180K	18	0.14	0.38	1.95	2.60
ASCD0503-220K	22	0.17	0.45	1.80	2.20
ASCD0503-270K	27	0.21	0.58	1.50	1.75
ASCD0503-330K	33	0.25	0.65	1.35	1.62
ASCD0503-390K	39	0.30	0.85	1.28	1.60
ASCD0503-470K	47	0.38	0.95	1.20	1.50
ASCD0503-560K	56	0.40	1.12	1.00	1.40
ASCD0503-680K	68	0.50	1.15	0.95	1.30
ASCD0503-820K	82	0.70	1.16	0.80	1.10
ASCD0503-101K	100	0.76	1.50	0.70	1.00

型号P/N	L(uH)	DCR(Ω)		I _{rms} (A)	I _{sat} (A)
		Typ	Max		
ASCD0504-1R0N	1.0	0.013	0.10	6.10	7.00
ASCD0504-2R2N	2.2	0.021	0.12	4.20	5.30
ASCD0504-3R3M	3.3	0.019	0.15	3.85	4.30
ASCD0504-6R8M	6.8	0.042	0.20	2.00	2.80
ASCD0504-100K	10	0.055	0.25	2.00	2.50
ASCD0504-120K	12	0.080	0.30	1.55	2.00
ASCD0504-150K	15	0.085	0.31	1.40	1.80
ASCD0504-180K	18	0.090	0.35	1.10	1.75
ASCD0504-220K	22	0.100	0.36	1.00	1.65
ASCD0504-270K	27	0.156	0.38	0.95	1.55
ASCD0504-330K	33	0.178	0.45	0.80	1.30
ASCD0504-390K	39	0.190	0.58	0.70	1.21
ASCD0504-470K	47	0.209	0.65	0.65	1.15
ASCD0504-560K	56	0.320	0.85	0.55	1.00
ASCD0504-680K	68	0.385	0.95	0.50	0.95
ASCD0504-820K	82	0.400	1.12	0.40	0.90
ASCD0504-101K	100	0.415	1.15	0.30	0.80
ASCD0504-121K	120	0.630	1.16	0.25	0.68
ASCD0504-151K	150	0.800	1.50	0.20	0.60