

型号P/N	L(uH)	DCR(Ω)		I _{rms} (A)	I _{sat} (A)
		Typ	Max		
ASCD0703-3R3M	3.3	0.016	0.10	5.2	7.0
ASCD0703-5R6M	5.6	0.032	0.12	4.30	5.3
ASCD0703-6R8M	6.8	0.028	0.15	2.81	4.30
ASCD0703-8R2M	8.2	0.040	0.20	2.45	2.80
ASCD0703-100K	10	0.05	0.25	2.10	2.50
ASCD0703-120K	12	0.07	0.30	1.50	2.00
ASCD0703-150K	15	0.08	0.31	1.40	1.80
ASCD0703-180K	18	0.09	0.35	1.28	1.75
ASCD0703-220K	22	0.10	0.36	1.20	1.65
ASCD0703-270K	27	0.15	0.38	1.10	1.55
ASCD0703-330K	33	0.17	0.45	1.00	1.30
ASCD0703-390K	39	0.18	0.58	0.95	1.21
ASCD0703-470K	47	0.20	0.65	0.85	1.15
ASCD0703-560K	56	0.28	0.85	0.72	1.00
ASCD0703-680K	68	0.33	0.95	0.55	0.95
ASCD0703-820K	82	0.41	1.12	0.50	0.90
ASCD0703-101K	100	0.48	1.15	0.40	0.80
ASCD0703-121K	120	0.54	1.16	0.31	0.68
ASCD0703-151K	150	0.75	1.50	0.25	0.60
ASCD0703-181K	180	0.90	2.00	0.20	0.58

型号P/N	L(uH)	DCR(Ω)		I _{rms} (A)	I _{sat} (A)
		Typ	Max		
ASCD0705-100K	10	0.030	0.10	3.5	4.30
ASCD0705-150K	15	0.040	0.12	3.00	3.80
ASCD0705-180K	18	0.052	0.15	2.50	3.20
ASCD0705-220K	22	0.066	0.20	2.25	2.70
ASCD0705-270K	27	0.080	0.25	2.00	2.50
ASCD0705-330K	33	0.093	0.30	1.95	2.40
ASCD0705-390K	39	0.107	0.31	1.82	2.20
ASCD0705-470K	47	0.120	0.35	1.65	2.00
ASCD0705-560K	56	0.165	0.36	1.43	1.85
ASCD0705-680K	68	0.200	0.38	1.40	1.65
ASCD0705-820K	82	0.250	0.45	1.15	1.48
ASCD0705-101K	100	0.260	0.58	1.00	1.2
ASCD0705-121K	120	0.300	0.65	0.85	1.30
ASCD0705-151K	150	0.380	0.85	0.76	1.10
ASCD0705-181K	180	0.450	0.95	0.65	1.00
ASCD0705-221K	220	0.60	1.12	0.50	0.85
ASCD0705-271K	270	1.11	2.00	0.45	0.80
ASCD0705-331K	330	1.26	2.56	0.40	0.75
ASCD0705-391K	390	1.65	3.00	0.30	0.71